



TYPE _____

AL-FE

BY WESTERN LIGHTING

**SLIM PROFILE
EXTRUDED ALUMINUM
FIRE ESCAPE SIGN**

SPECIFICATIONS

HOUSING:	Extruded 1/16", 6063 aluminum alloy.	FINISH:	Natural anodized aluminum "NA". White painted housing "WH". Black painted housing "BL". Medium bronze painted "MB".
INSCRIPTION:	Full 6" high x 3/4" stroke red letters on phosphorescent glass panel. Full-length arrows, when required, underneath inscription. Red on white "R/W". Green on white "G/W". Consult factory for special inscriptions and graphics "SG".	MOUNTING:	7/8" diameter knockouts are provided on top, side and back. Canopy kit included.
LAMPS:	Two 20T6 1/2/DC/IF specify "LL". Two 15T6 1/2/DC 145 volt "L15". Two 5 watt compact fluorescent "PL5". Note: current for two normal power factor PL-5 120 volt ballasts is 300 ma.	OPTIONS:	For down light specify "DL". Pendant mounting "-PND" (advise length)".
VOLTAGE:	Fluorescent 120 or 277. Incandescent available in 120 volt only.	CODES:	Complies with UL 924, NEC and Life Safety Code. Meets the Municipal Code of Chicago and approved by the Chicago Bureau of Fire Prevention.
		DIMENSIONS:	Height 9-1/8" Width 22 1/4" Depth 2 1/4" Canopy adds 9/16" to height.

ORDERING CODE

SERIES	INSCRIPTIONS	LAMPS	VOLT	FINISH	OPTIONS
AL-FE	+	+	+	+	+
	(*CODE)-R/W (*CODE)-G/W (*CODE)-SG *SEE BELOW	LL LL15 PL-5	120 277	NA WH BL MB	DL PND(LENGTH)
	CODE	FIRE ESCAPE SINGLE FACE		FIRE ESCAPE DOUBLE FACE	
	NO ARROWS	1		16	
	ARROW RIGHT	4		19	
	ARROW LEFT	7		19	
	DOUBLE ARROW	10		22	

© 1997 WESTERN LIGHTING INC
AL-FE-USA-1.5



WESTERN LIGHTING, INC.
2349 N. 17th Ave. • Franklin Park, IL 60131-3432
(847) 451-7200 • Fax: (847) 451-7275

