



AL

BY WESTERN LIGHTING

**SLIM PROFILE
EXTRUDED ALUMINUM
EXIT SIGN
LED, FLUORESCENT
AC ONLY**

SPECIFICATIONS

HOUSING: Heavy duty 1/16" 6063 aluminum alloy.

INSCRIPTION: Full 6" high x 3/4" stroke red letters on phosphorescent glass panel.
Other combinations available:
Red on White "R/W"
Green on White "G/W"
Consult factory for special inscriptions and graphics "S/G"

LAMPS: White LED 4.5 watt array "LED"
(5 YEAR WARRANTY)
Two 5 watt compact fluorescent, "PL-5"

VOLTAGE: Fluorescent: 120v or 277v

FINISH: Natural anodized aluminum "-NA"
White painted housing "-WH"
Black painted housing "-BL"
Medium bronze painted "-MB"
Anodized color, consult factory "-ANO"

MOUNTING: 7/8" diameter knockouts are provided on top, side and back. Canopy kit included.

OPTIONS: Pendant mounting
ADVISE STEM LENGTH "PND-(LENGTH)"

CODES: Complies with UL 924, NEC and Life Safety Code. Meets the Municipal Code of Chicago and approved by the Chicago Bureau of Fire Prevention (**Glass Panels only**). ETL listed.

DIMENSIONS: Stair and exit are the same size.
Canopy adds 9/16".

EXIT	
Height	9-1/8"
Width	13-3/4"
Depth	2-1/4"

ORDERING CODE

SERIES			VOLT		FINISH		OPTIONS
AL	+	+		+		+	
	(*Code)-RW (*Code)-GW SG *SEE BELOW	LED PL5	120 277		NA WH BL MB ANO		PND ST

	SINGLE FACE EXIT	DOUBLE FACE EXIT	SINGLE FACE STAIR	DOUBLE FACE STAIR
NO ARROWS	3	18	2A	17A
ARROW RIGHT	6	21	5A	20A
ARROW LEFT	9	21	8A	20A
DOUBLE ARROW	12	24	11A	23A

© 2014 WESTERN LIGHTING INC
AL-LED-2014-6



WESTERN LIGHTING, INC.
2349 N. 17th Ave. • Franklin Park, IL 60131-3432
(847) 451-7200 • Fax: (847) 451-7275

