



# CS-6-LC

BY WESTERN LIGHTING

## 6 VOLT WALL MOUNTED EMERGENCY LIGHTING UNIT

### SPECIFICATIONS

**HOUSING:** Compact size white painted 20-gauge steel, is easily mounted. Access to test switch and LED charge/AC indicator lamp are on the side.

**BATTERY:** Standard is 6 volt maintenance free sealed lead calcium cell that provides a maximum of 24 watts for 90 minutes operation. **"-LC24"**.  
For 36 watts @ 90 Minutes **"LC36"**  
Other extended run-times are available. Consult factory. **"-EXR"**

**HEADS:** Two metal heads specify **"-2M"** (standard).  
One metal head specify **"-1M"**  
No heads **"-0H"**  
Remote Head capability **"-RHC"**  
(Order remote head separately)

**LAMPS:** 12 watt Halogen sealed beam lamps are standard.

**CHARGER:** Dual-Voltage 120/277 Solid-state 6 volts DC design meets UL 924 recharge requirements, low voltage disconnect protects against deep discharge, line latch circuit included. Brown out protected.

#### OPTIONS:

**Battery Heater and thermostat**  
For Cold-Weather applications  
Activates at +50deg F **"-HTR"**  
Wired for one remote mounted head **"-1R"**  
Wired for two remote mounted heads **"-2R"**  
End Mounted heads **"-EMH"**  
For remote test by a hand held transmitter specify **"-RT"**  
Wire guard **"-WG"**

**CODES:** ETL listed. Complies with NEC and Life Safety Code.  
Meets City of Chicago requirements.

#### DIMENSIONS:

Length with top mount heads 10-5/8"  
Length with end mount heads 24-5/8"  
Height with top heads 12.0"  
Height with end mount heads 5.0"  
Depth 4-1/2"

### ORDERING CODE

SERIES	BATTERY	HEADS	OPTIONS
CS-6-LC	+ 24	+ 2M	+ HTR
	36	2M	EXR- (HOURS)
			RHC
			EMH
			RT



**WESTERN LIGHTING, INC.**  
2349 N. 17th Ave. • Franklin Park, IL 60131-3432  
(847) 451-7200 • Fax: (847) 451-7275

