



CG6

BY WESTERN LIGHTING

6 VOLT T-BAR CEILING MOUNTED EMERGENCY LIGHTING UNIT

SPECIFICATIONS

HOUSING: Compact size 5.25"wide X 23.75" long white painted 20-gauge steel, is easily mounted in a T-bar ceiling. Faceplate contains test switch and LED charge/AC indicator.

BATTERY: Standard is 6 volt maintenance free sealed lead calcium cell that provides a maximum of 36 watts for 90 minutes operation **"-LC36"**.

HEADS: Two metal heads specify **"-2M"**. Remote head capability **"RHC"** (Order remote head separately)

CHARGER: Dual voltage 120/277 input solid-state 6 volts DC design meets UL 924 recharge requirements, low voltage disconnect protects against deep discharge, line latch circuit included. Brown out protected.

LAMPS: 12 watt sealed beam Halogen lamps are standard.

OPTIONS: Wired for one remote mounted heads **"-1R"**. For remote test by a hand held transmitter specify **"-RT"**.

SELF-DIAGNOSTIC: Automatic monitoring of the function and maintenance of the system. **"-SD"**

CODES: ETL listed. Complies with NEC and Life Safety Code. Meets City of Chicago requirements.

DIMENSIONS:

Length	23.75"
Width	5.10"
Recess depth	5.50"

ORDERING CODE

SERIES	BATTERY	HEADS	OPTIONS
CG6	+ LC36	+ 2M	+
			RT Remote Test 1R 1 Remote head SD Self-Diagnostic



WESTERN LIGHTING, INC.
 2349 N. 17th Ave. • Franklin Park, IL 60131-3432
 (847) 451-7200 • Fax: (847) 451-7275

