



# LP/EM

BY WESTERN LIGHTING

**LOW PROFILE ONLY 8-5/8" HIGH**  
**IDEAL FOR OVER DOOR AND LOW**  
**CEILING AREAS**  
**2 HOUR BATTERY BACKUP**  
**EXIT OR DIRECTIONAL SIGN**  
**LED, OR FLUORESCENT**

## SPECIFICATIONS

<p><b>HOUSING:</b> 20-gauge, cold rolled steel is standard. Stainless Steel available specify <b>"-SS"</b></p> <p><b>INSCRIPTION:</b> Full 6" high x 3/4" stroke red letters on phosphorescent glass panel. <b>"-R/W"</b></p> <p style="padding-left: 20px;">Consult factory for special inscriptions and graphics <b>"-SG"</b></p> <p><b>LAMPS:</b> <b>White LED 4.5 watt specify "LED"</b>                  (5 yr LED warranty)                  For two 5-watt compact fluorescent <b>"-PLS"</b>                  For two 20T6 1/2/DC/IF (120V only) specify <b>"-LL"</b></p> <p style="padding-left: 20px;">For battery operation two #909 6-volt DC lamps are included.</p> <p><b>VOLTAGE:</b> <b>LED is available in 120v or/ 277v</b>                  Fluorescent 120 or 277, specify voltage</p> <p><b>FINISH:</b> White powder coat Standard <b>"-WH"</b>                  Black <b>"-BL"</b>                  Medium bronze <b>"-MB"</b>                  Brushed Stainless steel <b>"-SS"</b></p> <p><b>MOUNTING:</b> 7/8" diameter knockouts are provided on top, end and back. Standard canopy is included.</p>	<p><b>OPERATION:</b> Unit operates as a self-contained emergency system. Battery and charger are enclosed in the sign and meet latest UL 924 recharge requirements. Battery is lead calcium and sized to operate for a full two hours. Pilot light and test switch are located on the bottom of the unit.</p> <p><b>OPTIONS:</b> Battery Heater and Thermostat                  For cold weather applications                  Activates at +50 degrees F <b>"-HTR"</b>                  For Stainless steel construction specify <b>"-SS"</b>                  Easy mount canopy kit <b>"-EZCP"</b>                  Pendant mounting <b>"-PND/(stem length)"</b></p> <p><b>CODES:</b> ETL Listed. Complies with UL-924, NEC and NFPA-101 Life Safety Code.                  Approved by Fire Prevention Bureau, City of Chicago.</p> <p><b>DIMENSIONS:</b> Stair and exit are the same size.                  Height 8-5/8 "                  Width 17 "                  Depth 3-5/8 "                  Canopy adds 1/2" to height.</p>
---	--

## ORDERING CODE

SERIES	INSCRIPTIONS	LAMPS	VOLTAGE	FINISH	OPTIONS
<b>LP/EM</b>	<b>+ See Below</b>	<b>+</b>	<b>+</b>	<b>+</b>	<b>+</b>
	(*CODE)-R/W (*CODE)-G/W (*CODE)-SG	LED PLS	120 VOLTS 277 VOLTS (PL LAMPS ONLY)	WH BL MB SS	HTR EZCP PND/(length)
	<u>SINGLE FACE EXIT</u>	<u>DOUBLE FACE EXIT</u>	<u>SINGLE FACE STAIR</u>	<u>DOUBLE FACE STAIR</u>	
NO ARROWS	3	18	2A	17A	
ARROW RIGHT	6	21	5A	20A	
ARROW LEFT	9	21	8A	20A	
DOUBLE ARROW	12	24	11A	23A	



**WESTERN LIGHTING, INC.**

2349 N. 17th Ave. • Franklin Park, IL 60131-3432  
 (847) 451-7200 • Fax: (847) 451-7275

