



TYPE _____
PK-LED-EM

BY WESTERN LIGHTING

**LONG-LIFE LED LIGHT
 SOURCE, BATTERY BACK-UP
 SLIM PROFILE
 INJECTION MOLDED PLASTIC
 EMERGENCY EXIT SIGN**

SPECIFICATIONS

HOUSING: Injection molded plastic housing uses snap together components for quick assembly. Integral optical system insures even surface luminance.

INSCRIPTION: Full 6" high x 3/4" stroke red letters behind cut-out stencil face. Field-selectable Chevron indicators.

LAMPS: Fixture is illuminated internally by the use of an LED (light-emitting diode) light array. LED lamps require no maintenance and consume less than one watt per fixture. No visible LED lamps. For red letters specify "-R" For green letters specify "-G"

EMERGENCY OPERATION: Emergency Nickel-Cadmium battery back up is rated for 90 or more minutes of operation. Power consumption is 3 watts per fixture. LED AC on indicator and push-to-test switch is included.

VOLTAGE: 120v or 277v inputs are accommodated with dual-tap LED driver.

FINISH: White, U.V. stable thermoplastic UL V 94 fire rated.

MOUNTING: Knockouts are provided on top, side and back. Canopy kit is required for top or end mounting. Universal mount option permits single face or double face installation, canopy is included.



CODES: Complies with ANSI/UL 924, NEC and Life Safety Code. UL Listed.

OPTIONS: Remote test eliminates the need to manually push test switch, specify "-RT". Requires at least one remote transmitter, specify "-RTT".

DIMENSIONS: EXIT HOUSING
 Height 8-5/8"
 Width 12-1/8"
 Depth 1-3/4"
 Shallow Canopy adds 1" to height.

ORDERING CODE

SERIES	LAMP COLOR	FACES	VOLTAGE	OPTIONS
PK-LED-EM	+	+ U	+ 120/277	+
	R= Red LED G=Green LED	U = UNIVERSAL MOUNT, SF & DF WITH CANOPY		RT RTT



WESTERN LIGHTING, INC.
 2349 N. 17th Ave. - Franklin Park, IL 60131-3432
 (847) 451-7200 • Fax: (847) 451-7275

